



ZPMV2.E321090 Wiring, Printed - Component

Enhanced searching capability for this category can be found in UL's iQ Family of Databases (iq.ul.com).

[Page Bottom](#)

Wiring, Printed - Component

[See General Information for Wiring, Printed - Component](#)

EBH ELEKTRONIK BAUTEILE GMBH
BREITENLOHER STRABE 18
91187 ROTTENBACH
91187 ROTTENBACH, GERMANY

E321090

Type	Cond Width		Cond	SS/ DSO	Max	Solder		Max	Flame	Meets	C
	Min	Edge			Area	Oper	UL796	T			
	mm(in)	mm(in)	Thk	Diam	Limits	Temp	C	sec	Class	DSR	I
Multilayer (mass laminated) printed wiring boards.											
ebh-2	0.1 (0.004)	0.28 (0.011)	17 (0.67)	DS	25.4 (1.0)	260	20	130	V-0	All	-
Multilayer printed wiring boards.											
ebh-10	0.10 (0.004)	0.30 (0.012)	17 (0.67) Int:136	DS	88.9 (3.5)	288	10	130	V-0	All	-
ebh-11	0.10 (0.004)	0.10 (0.004)	17 (0.67) Int:68	DS	76.2 (3.0)	288	20	130	V-0	All	-
ebh-18	0.10 (0.004)	0.28 (0.011)	17 (0.67) Int:14	DS	25.4 (1.0)	260	20	130	V-0	All	0
ebh-21	0.07 (0.003)	0.21 (0.008)	17 (0.67) Int:102	DS	25.4 (1.0)	270	10	130	V-0	All	*
ebh-22	0.07 (0.003)	0.21 (0.008)	17 (0.67) Int:102	DS	25.4 (1.0)	270	10	130	V-0	All	*
ebh-3	0.08 (0.003)	0.08 (0.003)	12 (0.47) Int:70	DS	25.4 (1.0)	260	5	130	V-0	All	-
ebh-4	0.17 (0.669)	0.51 (0.020)	35 (1.38) Int:105	DS	50.8 (2.0)	288	20	130	V-0	All	-
ebh-6	0.06 (0.002)	0.18 (0.007)	17 (0.67) Int:68	DS	25.4 (1.0)	280	10	130	V-0	All	-
Single Layer Metal Base printed wiring boards.											
ebh-12	0.20 (0.008)	0.20 (0.008)	35 (1.38)	SS	76.2 (3.0)	288	20	130	V-0	All	-
ebh-13	0.20 (0.008)	0.60 (0.024)	35 (1.38)	SS	76.2 (3.0)	288	20	130	V-0	-	-
ebh-14	0.20 (0.008)	0.60 (0.024)	17.5 (0.69)	SS	76.2 (3.0)	288	20	130	V-0	-	-
Single layer printed wiring boards.											
ebh-1	0.09 (0.004)	0.27 (0.011)	17 (0.67)	DS	25.4 (1.0)	260	20	130	V-0	All	*
ebh-15	0.10 (0.004)	0.10 (0.004)	17 (0.67)	DS	76.2 (3.0)	288	20	130	V-0	All	-
ebh-17	0.10 (0.004)	0.28 (0.011)	17 (0.67)	DS	25.4 (1.0)	260	20	130	V-0	All	0
ebh-19	0.07 (0.003)	0.21 (0.008)	17 (0.67)	DS	50.8 (2.0)	270	10	130	V-0	All	*
ebh-20	0.07 (0.003)	0.21 (0.008)	17 (0.67)	DS	25.4 (1.0)	270	10	130	V-0	All	*
ebh-5	0.06 (0.002)	0.18 (0.007)	17 (0.67)	DS	50.8 (2.0)	280	10	130	V-0	All	-
ebh-7	0.10 (0.004)	0.30 (0.012)	34 (1.34)	SS	88.9 (3.5)	288	10	130	V-0	-	-
ebh-8	0.10 (0.004)	0.30 (0.012)	17 (0.67)	DS	88.9 (3.5)	288	10	130	V-0	▲	-
ebh-9	0.10 (0.004)	0.30 (0.012)	17 (0.67)	DS	88.9 (3.5)	270	10	130	V-0	All	-
Single layer printed wiring boards, flammability only Recognition.											
ebh-16	-	-	-	DS	-	288	20	-	V-0	-	-

* - CTI PLC is marked on individual board.



Marking: Company name or trademark identification or burning test classification. May be followed by a suffix to denote factory

Last Updated on 2012-02-17

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2013 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2013 UL LLC".